
HSX2320 Series



CONVETTORE
CONVECTOR
CONVECTEUR
KONVEKTOR
LUCHTVERHITTER
AQUECEDOR
ΘΕΡΜΟΠΟΜΠΟΣ
ΚΟΗΒΕΚΤΟΡ
FŰTŐBERENDEZÉS
KONVEKTOR
KONWEKTOR
KONVEKSJONSOVN
VÄRMEELEMENT
LÄMMITIN

De'Longhi

IT

pag. 4

EN


page 7

FR

page 10

DE

S.13

**NL**

pag. 16

ES

pág. 19

PT

pág. 22

EL

σελ. 25

RU

стр. 28

KZ

Бет. 31

HU

old. 35

CS

str. 38

SK

str. 41

PL

str. 44

HR

str. 47

SL

str. 50

BG

стр. 53

RO

pag. 56

ELECTRICAL CONNECTION (UK ONLY)

- A) If your appliance comes fitted with a plug, it will incorporate a 13 Amp fuse. If it does not fit your socket, the plug should be cut off from the mains lead and an appropriate plug fitted, as below.
 With alternative plugs not incorporating a fuse, the circuit must be protected by a 15 Amp fuse. If the plug is a moulded-on type, the fuse cover must be re-fitted when changing the fuse using a 13 Amp Asta approved fuse to BS 1362. In the event of losing the fuse cover, the plug must.
 NOT be used until a replacement fuse cover can be obtained from your nearest electrical dealer. The colour of the correct replacement fuse cover is that as marked on the base of the plug.
WARNING: Very carefully dispose of the cut off plug after removing the fuse: do not insert in a 13 Amp socket elsewhere in the house as this could cause a shock hazard.
- B) UK Plug specifications: please follow the instructions provided below.

IMPORTANT

The wires in the mains lead are coloured in accordance with the following code:

Blue: Neutral

Brown: Live

As the colours of the wires in the mains lead may not correspond with the coloured markings identifying the terminals in your plug, proceed as follows:

The blue wire must be connected to the terminal marked with the letter N or coloured black.

The brown wire must be connected to the terminal marked with the letter L or coloured red.

If you have a 3-pins plug, do not connect any wire to the "earth" terminal.

